



Headsets



DE-2500



TECHNICAL DATA

Headphone Section

Frequency Response: 16 - 21,000 Hz
 Driver: dynamic
 Acoustic Principle: closed
 Nominal Impedance: 100 ohms
 Continuous Power Rating: 100 mW
 Average Pressure on the Ear: ~ 6 N
 Weight w/o Cable: 270/200 g

Microphone Section

Microphone Type: electret
 Frequency Response: 40 - 18,000 Hz
 Polar Pattern: cardioid
 Nominal Impedance: 1000 ohms
 Sensitivity: 16.25 mV/Pa
 Phantom Power: 1.5 - 9 V
 Front-to-Back Ratio: 15 dB

The DE Series headsets are specifically designed for demanding applications such as language laboratories and intercom systems, where quality, reliability, and comfort are of utmost importance.

The virtually indestructible housings are made of a special flexible PE material. Soft, gentle ear pads provide comfort even for the longest lasting audio sessions.

The DE-2500 features an electret microphone with a very good front-to-back ratio and an integrated pop filter. The flexible yet unbreakable microphone boom is molded from a single die with the left headphone housing and can be bent into any required position.

The cable entry on these models is one sided and the inner wirings are completely concealed to avoid damage.

A special rugged round PU cable guarantees a long life cycle even under harsh working conditions. And the graduated height adjustable ear cups ensure a perfect fit for nearly all head sizes.



Virtually Indestructible!

DE-2400



TECHNICAL DATA

Frequency Response: 10 - 33,400 Hz
 Driver: dynamic
 Acoustic Principle: closed
 Nominal Impedance: 300 ohms
 SPL: 98 dB
 Continuous Power Rating: 100 mW
 Distortion: K2 < 0,13 % / K3 ≤ 0,0 %
 Design Principle: circumaural
 Average Pressure on the Ear: ~ 5,5 N
 Weight w/o Cable: 220 g
 Connector: 6.3 mm or 3.5 mm stereo
 Cable Length: 8 feet



C-202V

The C-202V headset with microphone and volume control has been thoroughly tested in the harshest learning environments in the world and has come through with shining colors. It sounds great too!

The integrated volume control allows individuals to listen in comfort at any level.

These lightweight units are comfortable to wear for hours at a time.



Speaker: 40mm Dynamic type
 Impedance: 32 ohms
 Sensitivity: 100dB 4dB
 Frequency: 20~20000Hz
 Max. Input Power: 100mW
 Microphone: condenser type
 Standard Operating Voltage: 4.5V
 Polar Pattern: cardioid
 Sensitivity: -60dB 3dB
 Frequency Response: 20~16000Hz
 Weight: 190g
 Cord length: 6 feet (1.8M)
 Connector: 3.5mm stereo plug x 2